

TECHNICAL DATA SHEET

FORTIS ADHESION PROMOTER

DESCRIPTION	A one component adhesion promoter for brush, roller or low pressure spray application.
USES	FORTIS ADHESION PROMOTER is developed for use as an adhesion promoter primer for glass and concrete substrates, especially highly polished surfaces, such as certain tiles.
FEATURES	A one pack system with low odour during installation and excellent adhesion to glass and cementitious substrates.
COLOUR	Clear
PACK SIZE	1lt and 5lt cans
SURFACE PREPARATION	Substrates need to be clean, dry and dust free. Light etching with citric acid / hydrochloric acid may be required to remove polishing residue from ground concrete.
APPLICATION	Apply in an even coat at 10-20 m ² per litre to wet the surface. Do not flood or puddle. Use mohair rollers, wide brush or low-pressure spray.

TECHNICAL DATA

Composition:	Silane solution
Film Thickness:	5 microns per coat DFT
Coverage Rate:	10-20 m ² per litre per coat
Touch Dry (Dust Free)	Approximately 2 hours @ 20°C
Top-Coating:	Recoat within one day. Ensure good ventilation. Apply polyurethane after 4 hours minimum cure.
Flashpoint:	12°C
Shelf Life:	6 months in unopened container
Clean up:	Warm water with detergent

SAFETY DATA

Please refer to Fortis Safety Data Sheet for Fortis Adhesion Promoter. Fortis Adhesion Promoter is safe if good working practices and proper application equipment is used. Caution should be taken as the material is flammable. Naked flames and smoking should not be permitted in the working area. Good industrial hygiene should be observed at all times - impervious gloves should be worn when handling coating. Avoid contact with skin.

Note:

Fortis Adhesion promoter contains solvents. It is recommended that positive air-supplied full face respirator be used if spraying.

Disclaimer

Fortis products should be used in accordance with the information contained here. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained here is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings office directly. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained here.